



DATA SHEET

Tough. Ready. Scalable.

IronWolf 110 SSD



The Seagate® IronWolf® 110 SSD is designed for everything business NAS, with 24x7 performance to handle multi-user environments across a wide range of capacities.



Take your NAS to the next level with the IronWolf 110 SATA SSD, providing pure performance in all-flash array or tiered cache NAS-enabled systems. This enterprise-grade SSD gives you increased durability and peace of mind.

Optimized to Be Tough

Boost the performance of NAS, which requires faster random access performance

Maintain fast, consistent performance for read-intensive and mixed workloads

Choose built-in drive monitoring with enabled NAS with IronWolf Health Management¹

Key Features and Benefits

- SATA 6Gb/s interface for easy deployment
- Seagate DuraWrite™ lossless data reduction technology
- Optimized with AgileArray firmware tuned specifically for NAS
- Power loss data protection circuit
- Enterprise-class reliability with 2M-hr. MTBF and a 5-year limited warranty

Best-Fit Applications

- All-flash array NAS
- Tiered caching on enabled NAS
- Creative pro NAS
- Small, medium enterprise NAS

Always Accessible, Always Ready

Require less energy to run on 24x7 NAS, and save on cooling and overall energy cost

Acquire the capacity and endurance to fit a range of applications and workloads

Scalable for Data Growth in NAS

Leverage a wide portfolio to fit your growing business needs

Depend on a 5-year limited warranty and included 2-year Data Recovery Services plan

¹ Coming soon on enabled NAS





Specifications					
Capacity	3.84TB	1.92TB	960GB	480GB	240GB
Standard Model	ZA3840NM10001	ZA1920NM10001	ZA960NM10001	ZA480NM10001	ZA240NM10001
Features					
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
NAND Flash Type	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC
Form Factor	2.5 in x 7mm	2.5 in x 7mm	2.5 in x 7mm	2.5 in x 7mm	2.5 in x 7mm
Performance					
Sequential Read (MB/s) Sustained, 128KB QD32 ¹	560	560	560	560	560
Sequential Write (MB/s) Sustained, 128KB QD32 ¹	535	535	535	535	345
Random Read (IOPS) Sustained, 4KB QD32 ¹	85000	90000	90000	75000	55000
Random R70R (IOPS) Sustained, 4KB QD32 ¹	60000	65000	50000	40000	30000
Random Write (IOPS) Sustained, 4KB QD32 ¹	45000	50000	55000	50000	30000
Average Read Latency (µs), 4KB QD1 ¹	175	160	155	155	155
Average Write Latency (µs), 4KB QD1 ¹	40	35	40	40	40
Endurance/Reliability					
Total Bytes Written (TB)	7000	3500	1750	875	435
Nonrecoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2000000	2000000	2000000	2000000	2000000
Warranty, Limited (years)	5	5	5	5	5
Power Management					
Power Supply	5V + 12V	5V + 12V	5V + 12V	5V	5V
+5/+12V Active Max Average Power (W) ²	3.5	3.4	3.2	2.7	2.3
Average Idle Power (W)	1.2	1.2	1.2	1.1	1.1
Environmental					
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40 to 85	-40 to 85	-40 to 85	-40 to 85	-40 to 85
Temperature Change Rate/Hr, Max (°C)	20	20	20	20	20
Shock, 0.5ms (Gs)	1000	1000	1000	1000	1000
Physical					
Height (in/mm, max)	7.00mm/0.276in	7.00mm/0.276in	7.00mm/0.276in	7.00mm/0.276in	7.00mm/0.276in
Width (in/mm, max)	70.10mm/2.760in	70.10mm/2.760in	70.10mm/2.760in	70.10mm/2.760in	70.10mm/2.760in
Depth (in/mm, max)	100.25mm/3.947in	100.25mm/3.947in	100.25mm/3.947in	100.25mm/3.947in	100.25mm/3.947in
Weight (lb/g)	79.4g/0.175lb	74.7g/0.164lb	74.3g/0.163lb	74.1g/0.163lb	70.6g/0.155lb
Carton Unit Quantity	10	10	10	10	10

¹ Performance data is based on testing under certain workload conditions and is subject to change. Performance assumes that a typical enterprise data workload has 80% entropy.

² 3.84TB, 1.92TB, and 960GB capacity points require 12V in addition to 5V power.



Ordering Information			
Specifications			
Retail Packaging	Box Dimensions	Master Carton Dimensions ¹	Pallet Dimensions
Depth/Length (in/mm)	1.004in/25.50mm	260.0in/10.236mm	47.992in/1219.00mm
Width (in/mm)	4.350in/110.50mm	163.0in/6.417mm	40.000in/1016.00mm
Height (in/mm)	5.344in/135.75mm	113.0in/4.449mm	46.181in/1173.00mm
Weight (lb/kg)	0.279lb/0.127kg	3.201lb/1.455kg	519.860lb/236.300kg
Quantities			
Boxes per Master Carton	10		
Master Cartons per Pallet	160		
Pallet Layers	8		

System Requirements	What's Included
---------------------	-----------------

- Windows® 10, Windows 8.1, Windows 7
- Linux
- Seagate® IronWolf® 110 SSD

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
WW	ZA3840NM10011	3.84TB	5	763649134061	8719706016674	10763649134068
WW	ZA1920NM10011	1.92TB	5	763649134054	8719706016667	10763649134051
WW	ZA960NM10011	960GB	5	763649134047	8719706016650	10763649134044
WW	ZA480NM10011	480GB	5	763649134030	8719706016643	10763649134037
WW	ZA240NM10011	240GB	5	763649134023	8719706016636	10763649134020

¹ Inner dimensions

seagate.com

© 2019 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. DuraWrite, the DuraWrite logo, and IronWolf are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import, and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1998.2-1906US June 2019